

- LEGEND
- ▣▣▣ CHANNELIZING DEVICES
 - ◀ SIGN

GENERAL NOTES

The maximum spacing between channelizing devices in a taper should be 12m; the maximum spacing between channelizing devices used to separate traffic should be 25m.


Traffic safety drums shall be used for channelization devices during nighttime operations. (See Special Provisions)

Channelizing devices shall be a minimum of 0.7m in height.

No encroachment on travelled lane. If encroachment is necessary, lane must be closed.

All signs shall be Black on Orange.

TYPICAL APPLICATION OF TRAFFIC CONTROL DEVICES FOR SHOULDER WORK ON FREEWAY OR EXPRESSWAY.

					REGION NO.	STATE	FED.AID PROJ.NO.	ENVIRONMENTAL AND ENGINEERING SERVICE CENTER	 Washington State Department of Transportation	SR 5 NEWAUKUM RIVER BRIDGE TO THURSTON COUNTY LINE		REFERENCE SHEET NUMBER	
DESIGNED BY					10	WASH	IM-0051(236)					SHEET 9 OF 13 SHEETS	
ENTERED BY					JOB NUMBER					CONTRACT NO.			
CHECKED BY					96X329								
PROJ. ENGR.													
DIST. ADM.										TRAFFIC CONTROL PLAN			
	DATE	DATE	REVISION	BY					cs\dgn\12738trf.dgn	31 JAN 97			